Eugen Lägler GmbH

Brushing/Structuring with TRIO B	rushing discs			
Brush Trimming				
stainless steel brushes	brass brus	hes	nylon brushes \Box	
New Installation / Renovation				
new installation	renova	tion		
Job Site Size				
surface (sqm):				
Installation				
wear layer of engineered wood floori	ng (mm):			
material thickness of solid wood floor	ring (mm):			
glued 🗌	nailed 🗌	screwed 🗌	floating 🗌	
with v-shaped joint				
Wood Species				
oak 🗌	walnut 🗌	spruce	pine 🗌	
other:				
Type of Wood Floor				
mosaic 🗌	strip 🗌	floorboard		
other:				
Laying Pattern				
cheq	uered/basketweave		herringbone 🗌	
	brick pattern		parallel pattern	
other:				
Old Surface Treatment (in case of renovation)				
	lacquer/finish		oil, natural□	
athan	hard wax oil		oil coloured	
other:				

Eugen Lägler GmbH

Sanding Procedure				
Procedure according to PS	T?		yes	no
Surface:				
Applied grit sequence?				
16	24	36	40	50
60 🗌	80	100	120	
Abrasive cutting material	used?			
corundum	zircon	silicium carbide	ceramic	diamond
Manufacturer of abrasive us	sed:		Lägler	
other:				
Machine used for sanding	g?			
	ELF	SUPERHUM.	PROFIT	TRIO
other:				
Edge:				
Applied grit sequence?				
16	24	36	40	50
60	80	100	120	
Abrasive cutting material	used?			
corundum	zircon	silicium carbide	ceramic	diamond
Manufacturer of abrasive us	sed:		Lägler	
other:				
Machine used for sanding	g?			
FLIP 🗌	ELAN			
other:				
Fine Sanding:				
Applied grit sequence?				
40	60	80	100	120
150 🗌	180			
Abrasive cutting material	used?			
corundum	zircon	silicium carbide	ceramic	diamond
I				

Manufacturer of abrasive us	sed:		Lägler	
other:				
Machine used for sanding?			TRIO	SINGLE
other:				
Sanding Screen:				
Was a work step executed v	with sanding screer	1?	yes	no
lf so, which grit was appl	ied?			
60 🗌	80	100	120	150
180	220			
And which machine was us	ed?		TRIO	
other:				
Had the floor been thoroug	hly vacuumed befor	re each work step?	yes	no
Brushing/Structuring Pro	ocedure			
Had the surface been water	popped before bru	shing?*	yes	no
If so, how often?				
1x	2x	3x		
Was the surface still wet wh	nen brushing?		yes	no
*) ATTENTION!	C		,	
Formation of puddles durin	g water popping m	ust be avoided.		
The surface should still be	damp when brushi	ng.		
Additional water popping is	NOT recommende	ed for softwood floors.		
Walking direction during	brushing:			
transverse to wood g	grain length	wise to wood grain \Box		cross sanding \Box
How many work steps we	ere performed with	n the brushing discs?		
1	2	3		
How many TRIO additional weights were used during brushing?		1	2	
Existing humidity during	brushing?			
Room humidity:		Wood humudity:		
Time required for brushir	ng (min.):			
L				

Eugen Lägler GmbH

Surface Treatment After Brushing		
lacquer / finish		oil, natural 🗌
hard wax oil		oil, coloured \Box
others:		
Manufacturer of surface treatment used:		
Had the surface been water popped before the surface treatment?*	yes	no
If so, was the surface completely dry during the surface treatment?	yes	no
*) ATTENTION!		
Surface must be completely dry		
Customer Satisfaction		
very satisfied satisfied		partly 🗌
dissatisfied very dissatisfied		
Instruction		
Had you been instructed by Lägler customer adviser?		
	yes	no
Remarks		
Pictures		
Are there any pictures available of the project?	yes	no