Eugen Lägler GmbH

Reason for your enquiry:			
Solid wood flooring	Engineered wood 🗌		
Subfloor			
Cement screed	Anhydride screed 🗌	Wooden beam 🗌	
Others:			
Floor heating			
Screed preparation			
Screed prepared with grit size:			
Wood species			
Oak 🗌	Beech 🗌	Maple 🗌	Walnut
Others:			
Type of wood floor			
Mosaic 🗌	Strip 🗌	Plank	
Others:			
Installation			
Laying pattern (e.g.:chequered pat	tern or brick house patt	ern):	
Glued	Nailed	Screwed	Floating 🗌
Others:			
Wear layer of engineered wood floo	oring:		
Material thickness of solid wood flo	oring in mm:		
Old surface (renovation)			
Finish/Lacquer	Penetrating oil 🗌 P	enetrating colour 🗌	
Others:			
Current state of the floor (e.g.: inter	nsive walk ways):		
Size of the room in sqm:	Size of	f the room in sqft:	

Eugen Lägler GmbH

Sanding			
Procedure according to PST®			
Used grit for field:			
Used grit for edges:			
Used grit for fine sanding:			
Used machines for field:			
Serial-Number, construction year and da	te of last maintanence:		
Used machines for edges:			
Serial-Number, construction year and da	te of last maintanence:		
Used machines for fine sanding:			
Serial-Number, construction year and da	te of last maintanence:		
Did you vacuum between all working	g-steps?		
Abrasives			
Aluminium Oxide 🗌	Zirconium 🗌	Silicium carbide 🗌	Ceramic 🗌
Others:			
Abrasives manufacturer:			
Filling			
How many times do you	1x 🗌	2x 🗌	3x 🗌
Finshing			
Finish/Lacquer 🗌	Penetrating oil	Penetrating colour	
Other:			
What kind of lacquer/oil did you use	?		
Specifics:			